



## MAXIMIZING THE POTENTIAL OF THE EXPONENTIAL UPGRADE.

# ZENITH X MAX HI VIZ CE

**STANDARD**  
EN 397 | 440V a.c. / -30°C / LD / MM  
EN 50365 (Class 0)  
CE 2008

EN 12492  
for the following clauses only:  
Shock energy absorption capacity  
4.2.1.2 front impact, 4.2.1.3 lateral  
impact, 4.2.1.4 rear impact  
4.2.2 | Penetration

**CATEGORY**  
III

**MATERIAL**  
EXTERNAL SHELL:  
HD Polypropylene  
  
INTERNAL SHELL:  
**Neopor® Cycled®** by BASF | EPS  
obtained from chemical recycling of  
plastic waste.  
  
HEADBAND:  
Soft PA Nylon

**TEMPERATURE OF USE**  
-30°C / +50°C

**WEIGHT**  
570 g

**SIZE**  
Adjustable – from 60 to 66 cm



WHE00131

○ 201 | ● 221

## TECHNOLOGIES

- **D-CORE TECHNOLOGY** Low-density Neopor® Cycled® EPS core protects from top impacts.
- **HD CROWN PROTECTION** High-density Neopor® Cycled® EPS inner shell protection designed for all-around impacts.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- **DRY+ LINER** Moisture-wicking fabric for enhanced comfort.
- **ADAPTIVE FIT SYSTEM** Size adjustment system that adapts to create a personalized, secure fit.
- **ADVANCED CHINSTRAP** 5 adjustment points and EN color-coded fastener.
- **COLOR-CODED FASTENER** The color of the fastener indicates the EN standard to which the chinstrap refers.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.
- **HI-VIZ DETAILS** High visibility color shell, luminescent lamp clips and reflective adhesives.

**3** YEARS  
GUARANTEE

**10** YEARS  
LIFE SPAN



SCAN FOR  
COMPLETE  
COLLECTION