



## **World's First Dual-Mode Self-Retracting Lifeline Fall Arrest and Rescue**

- **Exclusive design provides both fall arrest with assisted rescue capabilities and automatic self rescue for ultimate versatility.**
- **Fall arrest mode stops falls within few decimetres and limits the forces to 6kN or less for added safety.**
- **Assisted rescue procedures can then be implemented either at the mode selector or remotely with a First-Man-Up™ pole.**
- **Self rescue mode automatically lowers the user to the next level after a fall.**
- **Lightweight and long lasting durable reinforced plastic housing. Incorporates a built-in carrying handle for easy transportation.**
- **15 m cable extends and retracts automatically enabling the user to move around the work area protected.**
- **i-Safe™ Intelligent Safety System is built-into every unit to track inspections, control inventory and manage information.**
- **Designed to meet worldwide standards including CE EN360 and EN341.**

# ULTRA-LOK® RSQ SELF-RETRACTING LIFELINE WITH RESCUE



## Fall Arrest Mode Assisted Rescue

After setting the fall arrest mode, should a fall occur, the following will happen :

A speed sensing brake stops the fall, reduces forces imposed on the user to safe levels of 6kN or less and allows for assisted rescue to take place.



**Fall Arrest Mode Assisted Rescue by Hand**



**Fall Arrest Mode Assisted Rescue by Pole**



### Accessories for assisted rescue with 4.8m pole

**3500100**  
Assisted Rescue Tool Only



**3500102**  
First-Man-Up™ Pole with Assisted Rescue Tool

**These Assisted Rescue Options "engage" the Automatic Rescue Mode.**  
Traditional assisted rescue operations may also be conducted.

## Automatic Rescue Mode Self Rescue Descent

After setting the automatic rescue mode, the device will operate like a descender, should a fall occur, the following will happen :

A speed sensing brake slows the fall, then instantly a centrifugal brake activates, lowering the user at a controlled speed to the next level or ground.



**Automatic Rescue Mode Self Rescue/Descent**



## Ultra-Lok® RSQ Models - Self-Retracting Lifeline with rescue

- 3504553:** 15m length, galvanised cable
- 3504554:** 15m length, stainless steel cable
- 3504555:** 15m length, stainless steel cable and hook

- Accessories:** **3500100:** Assisted Rescue Tool  
**3500102:** First-Man-Up™ Pole with Assisted Rescue Tool

### Specifications:

**Rated capacity:** 34kg to 141kg **Maximum arresting force:** 6 kN **Descent Speed:** 1 m/s **Length of cable:** 15m **Size:** 20cm wide 29cm long, 9cm thick **Weight:** 8.5kg **Housing Material:** 2 pieces, thermoplastic composite **Cable material:** 5mm, 7x19 galvanised cable **Snap Hook:** Zinc plated alloy steel, self locking and swiveling, 22.2kN tensile strength **Standards:** Meets CE EN 360 and EN341.

**Capital Safety Group EMEA**  
Le Broc Center - Z.I. 1<sup>re</sup> Avenue - BP15  
06511 Carros le Broc Cedex - France  
Tél : +33 (0) 4 97 10 00 10 - Fax : +33 (0) 4 93 08 79 70  
[www.capitalsafety.com](http://www.capitalsafety.com) • [information@capitalsafety.com](mailto:information@capitalsafety.com)

**Capital Safety Northern Europe Ltd**  
7, Christleton Court - Stuart Road  
Manor Park - Runcorn - Cheshire - WA7 ST - UK  
Tel : +44 (0) 1928 571324 - Fax : +44 (0) 1928 571325  
[www.capitalsafety.com](http://www.capitalsafety.com) • [csgne@capitalsafety.com](mailto:csgne@capitalsafety.com)

Ref.: A01RSQTDEN Ind.0