

TECHNICAL DATA SHEET

FS242

LITE HARNESS

The FALL SAFE® FS242 - LITE HARNESS is the best selling ultra light harness. With low leg straps for improved comfort, this harness has an unique design and new impact resistant plates at its sides, to allow a comfortable fitting.

The airflow through all the harness layers is assured by the new and improved Croc 2.0 padding. This innovation also allows for a lighter and more ergonomic final product, that is extremely comfortable for use for several hours.

With reflective and extra breathable fabric, the FS242 combines the lightness of its composition with the FALL SAFE® quality assurance.





EAN CODE	SIZE	WEIGHT (KG)
5605423570809	S/M	0,9
5605423570816	L/XL	1,0
5605423570823	XXL	1,1

APPLICATIONS Access platforms | Construction | Roof works | Scaffolding





STANDARDS



INTENSITY OF USE





EN361:2002



TECHNICAL DATA SHEET

FS242 LITE HARNESS

FEATURES



DHYSICAL DRODEDTIES		
PHYSICAL PROPERTIES		
Metal parts	Aluminium	
Webbing	PES HP Water repellent	
Loops	Dorsal loop	
	2 front loops for fall arrest	
Buckles	IZY Quick connect buckles	
Padding	Croc 2.0	
Adjustment points	5 points	
Fall arrest indicators	Yes	
OTHER INFORMATION		
Device lifespan	10 years	
Max. Load	<140 KG	
Inspection requirement	Yearly	
Traceability	Serial Number/ RFID/ QR Code	
Manual Instructions	www.fallsafe-online.com +351 252 480 060	