


FS242EVO LITE EVO - FALL ARREST HARNESS


The FS242EVO – LITE EVO – FULL BODY HARNESS is an ultralight harness. With low leg straps for improved comfort, this harness has a unique design and new impact resistant plates at its sides, to allow a comfortable fitting. The airflow through all the harness layers is assured by the new and improved Croc 3.0 padding. This innovation also allows for a lighter and more ergonomic final product that is extremely comfortable for use for several hours. With reflective and extra breathable fabric, the FS242EVO combines the lightness of its composition with the FALL SAFE® quality assurance. It has 1 back loop for attachment point (A - EN361) for fall arrest as well 2 front loop (½ A + ½ A - EN361).



EAN CODE			SIZE			WEIGHT (KG)			APPLICATIONS		
5605423808100			S/M			1 (aprox.)			Roof works Scaffolding Construction		
5605423808094			L/XL			1.2 (aprox.)					
5605423808148			XXL			1.5 (aprox.)					
INTENSITY OF USE						STANDARDS					
Occasional use						CE EN361:2002					
<input type="radio"/> <input type="radio"/> <input checked="" type="radio"/>											

FS242EVO LITE EVO - FALL ARREST HARNESS

FEATURES



PHYSICAL PROPERTIES

Webbing 43 mm (black and lime)	Material 100% polyester Width (nom): 43.75 (+/- 1.25mm) Breaking Strength (min): 2300kg Weight (nom): 54g/m Thickness: 1.25mm Dye treatment: Disperse
IZY buckle	Aluminium Breaking Strength (min): 18kN 9kN
3 bars buckles	Steel alloy with lacquered finish
Loops (EN361)	Front loop - "1/2 A + 1/2 A" (PES+PA)/ Back loop - "A" (PES)
Adjustment points	4 points
Fall arrest indicators	Yes
Thread (gray)	100% polyester Breaking force: 17850 cN (ISO DIN EN ISO 2062)
Thread (black)	100% polyester Tensile strength (ISO 2062): 4460 cN

OTHER INFORMATION

Device lifespan	10 years
Max. Load	<140 KG
Inspection requirement	Yearly
Traceability	Serial Number/ QR Code
Manual Instructions	www.fallsafe-online.com +351 252 480 060