









# **RSGSAFETY.COM**













The T-Air is a unique battery-powered motor unit that can be used with a wide choice of approved filters and head tops. The T-Air is designed for the widest possible application in which a high(er) protection level and comfort is required. This applies particularly to work that is hard, warm, of long duration and requires a high protection and comfort level. The T-Air can be incorporated with a visor, hood, helmet combination or full face mask. The unit is equipped with class 2 filters, and the filtered air is fed through a strong flexible hose to the headpiece. The over pressure generated prevents surrounding pollutants from penetrating into the headpiece. A triple warning device assures the user of a safe

The T-Air<sup>®</sup> PAPR is waterproof and incorporates a full color LED display, triple alarm, multiple language settings as well as a data logging function that automatically saves usage and performance information, making archiving much easier. The microprocessor also allows your authorized RSG service center to carry out diagnostic tests and saves the complete service history.

- CONSTANT CONTROLLED AIRFLOW
- DUST & WATER PROOF (IP65)
- EXCHANGEABLE BATTERY
- RECHARGEABLE LITHIUM BATTERY
- TRIPPLE ALARM
- FULL LED DISPLAY
- NO CALIBRATION
- FULL RANGE OF CLASS 2 FILTERS
- DEDICATED THREAD CONNECTION

### T-Air<sup>®</sup> PAPR Features

- Electronically controlled constant airflow of 160 l/min
- Full LED display of battery status and filter clogging
- Multiple language settings
- Visual, vibration and acoustic alarm
- low battery and clogged filters alarm
- Average operating time of over 14 hours per charge
- Rechargeable Li-Ion battery
- Removable battery for charging- or outside the unit
- IP65 construction; dust and waterproof for easy decontamination
- Automatic closure of filter ports when changing filters
- Extremely low maintenance costs over the life of the device
- Full range of masks for various types of faces in TPE, Neoprene and Silicone
- No calibration required



T-Air® PAPR

614060 | NPF 500







614061 | NPF 500



615150 | NPF 10

614150 | NPF 50





TOTAL RESPIRATORY

## **T-AIR WELDING HEADTOPS**



T-Air® PAPR



T-AIR <sup>®</sup> WELD 500		T-AIR <sup>®</sup> WELD 820		T-AIR <sup>®</sup> WELD EUROMASKI	
Size	NPF 50 90*110 (ADF or Fixed shade) 51*108 (Flip up)	Size	<b>NPF 50</b> 95*85 (ADF)	Size	NPF 50 Standard shade 1.7 + 8
Standard: Part #:	EN12941 TH2P 615250	Standard: Part #:	EN12941 TH2P 614260	Standard: Part #:	EN12941 TH2P 614270



TECHNICAL SPECIFICATIONS		
Airflow	Constant 160 I/min	
Battery	Li-lon	
Charging	Inside or outside the unit	
Charging time battery	<3 hours	
Operating times P3	> 15 hr	
International Protection Code	IP 65* (Shower proof)	
Filter connection	EN148-1 dedicated	
Weight unit	800 gr	
Weight battery	700 gr	
Noise level (dB)	approx. 70 dB(A)	
Low flow warning	Visual / Acoustic /	
	Vibration	
Low battery warning	Yes	
Operating/Storage conditions	-10 °C to +50 °C	
Operating/storage area humidity	≤95 % relative humidity	
Approvals	EN12941:2008	
	EN12942:2008	
Notified Body	CE0158	

## T-Air<sup>®</sup> PAPR 2 or 3 filters

The unit is standard supplied with various parts as:

- battery
- charger
- comfort belt with safety buckle
- manual air\_ow indicator
- complete user instruction

Furthermore there are optional accessories available: Please contact your distibutor RSG for a complete demonstration





#### **AVAILABLE FULL FACE MASKS – READY PACKS & FILTERS**



T-AIR® PAPR DECON – READY PACK WITH 400SERIES FULL FACE MASK | NPF 2000Material:Neoprenen or SiliconeSizeM/LStandard:EN136 Class 2 & EN12942 TM3POrder number:650103-01T-AIR® PAPR DECON – READY PACK WITH 500SERIES FULL FACE MASK | NPF 2000Material:TPE or SiliconeSizeM/LStandard:EN136 Class 2 & EN12942 TM3POrder number:650103-02



Standard:EN136 Class 2 & EN12942 TM3POrder number:650103-02T-AIR® PAPR DECON – READY PACK WITH 700SERIES FULL FACE MASK | NPF 2000Material:SiliconeSizeM/LStandard:EN136 Class 3 & EN12942 TM3POrder number:650103-03



T-Air® PAPR

401209 A2P3



401215 A2B2P3

401216 A2B2E2P3



401217 A2B2EK22P3





401218 A2B2E2K2HgP3



RSG Safety BV Marinus Dammeweg 38 5928 PW VENLO The Netherlands Tel: +31 (0) 84 487 0395 www.rsgsafety.com sales@rsgsafety.com

RSG Safety France 6 AV DE L'ARMEE D'AFRIQUE 13100 AIX EN PROVENCE France

Tel: +33 (0) 484 80 01 25 www.rsgsafety.com sales@rsgsafety.com Distributor: